

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



(51) International Patent Classification 7 : B01J 19/00		A2	(11) International Publication Number: WO 00/44491
			(43) International Publication Date: 3 August 2000 (03.08.00)
(21) International Application Number: PCT/US00/02233 (22) International Filing Date: 28 January 2000 (28.01.00) (30) Priority Data: 60/118,377 29 January 1999 (29.01.99) US (71) Applicant: ILLUMINA, INC. [US/US]; Suite 200, 9390 Towne Centre Drive, San Diego, CA 92121 (US). (72) Inventor: LEBL, Michael; 6161 Arnoldson Court, San Diego, CA 92122 (US). (74) Agents: BREZNER, David, J. et al.; Flehr Hohbach Test Albritton & Herbert LLP, Suite 3400, 4 Embarcadero Center, San Francisco, CA 94111-4187 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>	
(54) Title: APPARATUS AND METHOD FOR SEPARATION OF LIQUID PHASES OF DIFFERENT DENSITY AND FOR FLUOROUS PHASE ORGANIC SYNTHESSES (57) Abstract A simple, efficient apparatus and method for separating layers of immiscible or partially miscible liquids useful in methods of high-throughput combinatorial organic synthesis or parallel extraction of large libraries or megaarrays of organic compounds is disclosed. The apparatus and method are useful, whether as part of an automated, robotic or manual system for combinatorial organic synthesis or purification (extraction). In a preferred embodiment, an apparatus and method for separating layers of immiscible or partially miscible liquids compatible with microtiter plate type array(s) of reaction vessels is disclosed. Another application of centrifugation based liquid removal was found for washing the plates in biological assays or synthesis on modified substrates.			

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	BS	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**APPARATUS AND METHOD FOR SEPARATION OF LIQUID PHASES OF
DIFFERENT DENSITY AND FOR FLUOROUS PHASE ORGANIC SYNTHESIS**

5 This application is a continuing application of U.S.S.N. 60/118,377 filed January 28, 1999.

FIELD OF INVENTION

10 The present invention relates to the field of devices and methods for chemical synthesis, analysis, and biological screening. More particularly, the present invention relates to a simple efficient apparatus and method for separation of immiscible or partially miscible liquid phases of different density in high-throughput, organic synthesis, or for removal of liquid from the vessels (washing). The present invention is particularly applicable for high-throughput combinatorial synthesis of organic molecules, whether as part of an automated or a manual procedure.

BACKGROUND OF THE INVENTION

15 Solid phase synthesis of organic molecules is the method of choice for preparation of libraries and compound megaarrays, which are currently being applied for screening in the quest to find new drugs or pharmaceutical lead compounds, i.e., compounds which exhibit a particular biological activity of pharmaceutical interest, and which can serve as a starting point for the selection and synthesis of a drug compound, which in addition to the particular biological activity of interest has pharmacologic and toxicologic properties suitable for administration to animals, including humans.

20 Fluorous synthesis is in its principle similar to solid phase synthesis. In fluorous synthesis the certain component of the reaction (starting material, reagent, or product) is preferentially retained in the fluorine atoms containing phase due to its high content of fluorine atoms. Fluorous phase is usually the high density one and therefore it can be separated as the lower phase in the multiphase system. Manual synthesis requires repetitions of several relatively simple operations of addition of reagents, 25 incubation and separation of liquid phases. This character of the synthetic process renders it optimal for automation.

Several designs of automated instruments for combinatorial synthesis utilizing solid phase synthesis have appeared in the patent and non-patent literature. However, there is no instrument designed for

the fluororous synthesis, since the simple principle of separation of phases by filtration is not applicable.

5 The productivity of automated instruments can be dramatically improved by use of disposable reaction vessels (such as multititer plates or test tube arrays) into which reagents are added by pipetting, or by direct delivery from storage containers. The optimal storage vehicle is a syringe-like apparatus of a material inert to the chemical reactants, etc., e.g., a glass syringe, allowing the storage of the solution without any exposure to the atmosphere, and capable of serving as a delivery mechanism at the same time. See U.S. Patent Application Serial No. 08/815,975. An alternative technique based on the removal of upper layer of liquid by suction from the surface above the separated layers is limited to the arrays of up to a hundred of suction needles. (For similar situation in solid phase synthesis see U.S. Patent Application Serial No. 08/815,975). The present application is an improvement upon U.S. Patent Nos 5,202,418, 5,338,831, 5,342,585, and U.S. Patent Application Serial No. 08/815,975 which describe placement of resin in polypropylene mesh packets and removal of liquid through the openings of these packets, or removal of the liquid from the pieces of porous textile-like material by centrifugation, or removal of liquid phase from the solid phase by centrifugation of tilted plates. Liquid removal by centrifugation was described and is the subject of several publications (see the book "Aspects of the Merrifield Peptide Synthesis" by Christian Birr in the series Reactivity and Structure Concepts in Organic Chemistry vol. 8, K. Hafner, J.-M. Lehn, C.W. Rees, P. von Rague, Schleyer, B.M. Trost, R. Zahradnik, Eds., Springer-Verlag, Berlin, Heidelberg, New York, 1978, and German Patent Application P 20 17351.7, G. 70 13256.8, 1970. These references describe the use of centrifugation for liquid removal from slurry of solid phase particles in a concentric vessel equipped with a filtration material in its perimeter and spun around its axis. See also WO99/25470, hereby expressly incorporated by reference in its entirety.

25 None of the prior art contemplates the separation of two (or more) immiscible, or partially miscible liquids of different density by removal of lighter layers of liquids by creation of "pockets" from which material cannot be removed by centrifugal force. This technique can be used in situations where multiplicity of products are to be extracted in parallel (e.g. in parallel purification of products of combinatorial synthesis). However, there is a need for a simple, efficient means of separating liquid phases during fluororous phase synthesis of organic molecules, particularly a method amenable to use with automated methods for such syntheses.

30 Furthermore, complete removal of the liquid from the multiplicity of vessels by spinning the array of wells attached with "reverse tilt" (tilting away from the axis of rotation) can find its application in biological assays where fast repeated washings of surface bound reagents or cells are required, and in applications where synthesis is done directly on the surface of the reaction vessels.

SUMMARY OF THE INVENTION

In accordance with the above objects, the present invention provides methods for elimination of a liquid phase from reaction vessels comprising positioning a plurality of reaction vessels containing a liquid or mixture of liquids in a holder on the perimeter of a centrifuge rotor. The holder, and thus the reaction vessels, are held in a tilted position with a tilt away from the axis of rotation. The rotor is then spun at a speed that expels the liquid from the vessels. This method of elimination can be used during solid-phase organic synthesis, for example synthesis of peptides or nucleic acids. Optionally, these steps can be repeated. Similarly, the reaction vessels may be contained in a microtiter plate or the reaction vessel may be a microtiter plate.

The expelled liquid can be collected in a collection pocket in the holder having a volume sufficient to collect and retain any liquid expelled from the vessels, or can be collected in a waste reservoir in or outside of the centrifuge.

In an additional aspect, the invention provides methods of synthesis of compounds comprising providing a reaction vessel containing a first building block coupled to the vessel itself. The vessel is then positioned in a holder on the perimeter of a centrifuge rotor. A second building block is added to the vessel under conditions that allow the coupling of the first and second building blocks, and the rotor is spun at a speed sufficient to expel the liquid from the vessel. Optional additional steps of repeating the procedure or washing steps can also be included. The building blocks can include amino acids and nucleosides.

In a further aspect, the invention provides methods for separating at least two immiscible or partially miscible liquids comprising positioning a plurality of reaction vessels containing the liquids in a holder on the perimeter of a centrifuge rotor. The rotor is then spun at a speed such that the lower layer of the multiphase system is retained in a "pocket" of the vessels and the upper layer is expelled from the vessels.

In an additional aspect, the invention provides apparatus comprising a centrifuge comprising a rotor designed to hold reaction vessels at a tilt away from the axis of rotation and a waste reservoir connected to the centrifuge to hold liquids expelled from the reaction vessels. In one embodiment, the waste reservoir is connected to the centrifuge with a tube. The apparatus may optionally comprise a liquid distribution system and a computer processor.

BRIEF DESCRIPTION OF THE FIGURES

The present invention can be understood more completely by reference to the following detailed description, examples, appended claims and accompanying figures.

Fig. 1A, 1B and 1C illustrate separation of two immiscible or partially miscible liquid phases in a

"pocket" of the vessels and expulsion of upper liquid layer achieved according to the method of the invention. Fig. 1A illustrates the lower liquid phase and upper liquid phase in the vessel prior to centrifugation. Fig. 1B and 1C illustrate the pocket containing retained lower liquid phase layer during spinning (and removal of the upper liquid layer).

5 Fig. 2A, 2B and 2C illustrate the path of liquid removed from a vessel, such as a well of a microtiter plate by centrifugation. The straight lip at the upper end of each well of the microtiter plate prevents the liquid from entering the well closer to the edge of a centrifugal plate - this well is higher and the lip wall is tilted in the direction to the bottom of the plate. The large arrow represents the vector resulting from centrifugal and gravitational forces. The small arrow with thin trailing line illustrates the direction
10 of the flow of liquid removed.

Fig. 3A and 3B illustrate an alternative embodiment of the invention in which a vessel having a lip facing inward when spun according to the method of the invention "creates" a "pocket" in which the lower liquid phase is retained.

15 Fig. 4A, 4B and 4C illustrate the situation in which wells are tilted in "reverse" tilt and no "pocket" is formed during centrifugation. The result is the complete removal of all liquid from the wells.

Fig. 5 shows the UV spectra of wells before and after two steps of parallel extraction proving complete elimination of contamination by aromatic hydrocarbon.

5. DETAILED DESCRIPTION OF THE INVENTION

20 For clarity of disclosure, and not by way of limitation, the detailed description of this invention is presented herein with respect to figures that illustrate preferred embodiments of elements of this invention. However, this invention includes those alternative embodiments of these elements performing similar functions in similar manners that will be apparent to one skilled in the art from the entirety of the disclosure provided. In addition, all references disclosed herein are incorporated by reference in their entirety.

25 The present invention is based on a discovery of a simple efficient means for separation of two (or more) immiscible, or partially miscible liquids of different density, e.g., removal of upper layer or layers of liquid from lower layer, used for parallel extraction and/or in fluoruous phase organic syntheses. In one embodiment of the invention, the fluoruous phase organic synthetic protocol utilizes widely available, disposable reaction vessel arrays, such as microtiter style plates. In an alternative
30 embodiment of the invention, the synthetic protocol utilizes a vessel with a lip facing inward (see Fig. 2) spun around its axis to create a "pocket" in which the lower layer of the multiphase system is retained. According to the present invention, however, any vessel or array of vessels or plurality of

arrays of vessels which can be placed in a tilted position on the perimeter of a centrifuge, can be used in the method of the invention. The method of the invention for separating of two (or more) immiscible, or partially miscible liquids of different density during a parallel extraction and/or in fluorous phase organic synthetic process comprises: (1) positioning a reaction vessel or an array of reaction vessels, such as a microtiter plate having an array of reaction wells, said vessel(s) containing a multilayer system of liquid phases, on the perimeter of a centrifuge rotor in a tilted position; and (2) spinning the rotor of the centrifuge at a speed so that the lower layer fills a "pocket" of the vessels and the upper liquid phases are expelled from the vessels. In one embodiment of the invention, the rotor is spun at a speed so that the centrifugal force on the radius corresponding to the reaction vessels which are closest to the axis of rotation is significantly greater than the force of gravity, and the lower layer forms a "pocket" of the vessels and the upper layers are expelled from the vessels. The volume of a "pocket" is determined by: (i) the degree of the tilt, (ii) the speed of rotation, and (iii) the distance of the particular reaction vessel from the axis of rotation. The appropriate combination of these factors determines the volume of residual liquid retained in the pocket and therefore completeness of upper layer removal. However, since it is desired that all reaction vessels in a multivessel arrangement of a reaction block (such as a microtiter plate) should undergo the removal of the upper layers of liquid to the same degree, it is important that the angle of the liquid surface in the "pocket" of the reaction vessels during the centrifugation is as close to 90 degrees with respect to the center of rotation as possible. In one embodiment, the removed liquid phase is collected on the wall of the centrifuge. In an alternative embodiment, the removed liquid phase is collected in a "collecting pocket" or a series of "collecting pockets" attached at the perimeter of the centrifuge rotor. The apparatus of the invention comprises a holder adapted to attaching a reaction vessel or an array of reaction vessels, e.g., a microtiter plate, to a rotor of a centrifuge, said holder comprising one or more indentations or groves designated "collecting pockets" positioned along one side of said holder said collecting pockets having a volume sufficient to collect and retain any liquid expelled from the reaction vessels, e.g./ the wells of the microtiter plate, when the holder and attached reaction vessels are spun by the centrifuge rotor. According to the invention, the holder can hold a single or individual microtiter plate or a plurality of microtiter plates, each plate comprising an array of vessels. One or more of the holders can be attached to the rotor of a centrifuge. In another embodiment, the apparatus of the invention is an automated integrated apparatus or system for parallel extraction and/or for fluorous phase chemical synthesis, comprising: (a) a centrifuge in which an array of reaction vessels suitable for parallel extraction and/or for fluorous phase organic synthesis can be spun in a tilted position; (b) a liquid distribution device; and (c) a computer for processing a program of instructions for addition of liquid phase to and removal, via centrifugation, of upper layer liquid phase from the reaction vessels according to the program.

In general, the methods and apparatus of the invention find use in combinatorial chemical synthesis. By way of introduction, combinatorial chemistry synthesis protocols prescribe the stepwise, sequential addition of building blocks to intermediate and/or partially synthesized intermediate compounds in

order to synthesize a final compound. In solid-phase synthesis, final compounds are synthesized attached to solid-phase supports that permit the use of simple mechanical means to separate intermediate, partially-synthesized intermediate compounds between synthetic steps. Typical solid-phase supports include beads, including microbeads, of 30 microns to 300 microns in diameter, which are functionalized in order to covalently attach intermediate compounds (or final compounds), and made of, e.g., various glasses, plastics, or resins.

WO 99/25470, hereby incorporated by reference, describes the use of a centrifuge in solid-phase synthetic reactions, wherein particles of solid phase (microbeads) are contained in reaction vessels such as microtiter plates. Synthesis is achieved by the stepwise addition of "building blocks" of the biopolymer, followed by centrifugation that drives the liquid phase out of the reaction vessels yet traps the solid phase in "pockets".

This general idea can be applied to differential phase synthetic reactions as well. While described for fluorous synthesis, one of skill in the art will appreciate that these techniques work for other phase-dependent synthetic methods as well.

The principle of fluorous phase synthesis is very similar to solid phase synthesis. In fluorous phase synthesis one of the reagents is attached to a high fluorine content block ("fluorous tail"), which assures that this reactant will always have a tendency to stay in fluorocarbon based solvent layer. Due to the fact that some fluorocarbon based solvents are not miscible (or only partially miscible) with both organic solvents and water and that this phase is in most cases the phase with the highest density, its properties can be used to mimic the solid phase principle of synthesis. Due to the fact that fluorous phase synthesis technology is at its very early stage of development, the general process for application in the combinatorial synthesis can be only speculated on. Fluorous phase combinatorial synthesis should proceed according to the following steps. In a first step, reaction vessels are charged with a fluorous phase, e.g. benzotrifluoride, and the first component of the synthesis (sometimes referred to herein as "the first building block") with attached "fluorous tail" (block containing high proportion of fluorine atoms) is delivered to all wells. Subsequently, a plurality of building block addition steps are performed, all of which involve repetitive execution of the following substeps, and in a sequence chosen to synthesize the desired compound. First, a sufficient quantity of a solution containing the building block moiety (e.g. the "second building block", "third building block", etc.) selected for addition is accurately added to the reaction vessels so that the building block moiety is present in a molar excess to the intermediate compound (compound with fluorous tail). The reaction is triggered and promoted by activating reagents and other reagents and solvents, which are also added to the reaction vessel. The reaction vessel is then incubated at a controlled temperature for a time, typically between 5 minutes and 24 hours, sufficient for the building block addition reaction or transformation to go to substantial completion. Optionally, during this incubation, the reaction vessel can be intermittently agitated or stirred. Finally, in a last substep of building block addition, the

reaction vessel containing the fluorous phase with intermediate compound attached to fluorous tail is prepared for addition of the next building block by removing the reaction fluid and thorough washing and reconditioning the fluorous phase by washing (repetitive addition and removal by centrifugation) with water and/or organic solvents. The limitation is that the fluorous phase must form always the lower phase of the system, which can be multilayer (multiphase).

Washing typically involves three to seven cycles of adding and removing a wash solvent. Optionally, during the addition steps, multiple building blocks can be added to one reaction vessel in order to synthesize a mixture of compound intermediates attached to one fluorous tail, or alternatively, the contents of separate reaction vessels can be combined and partitioned in order that multiple compounds can be synthesized in one reaction vessel.

After the desired number of building block addition steps, the final compound is present in the reaction vessel attached to the fluorous tail. The final compounds can be utilized either directly attached to the fluorous tail, or alternatively, can be cleaved from the fluorous tail and purified by extraction. Examples of fluorous phase synthetic protocols can be found in the following references: Curran, D.P. (1996) Combinatorial organic synthesis and phase separation: Back to the future. *Chemtracts:Org. Chem.*, 9, 75-87; Curran, D.P., & Hoshino, M. (1996) Stille couplings with fluorous tin reactants: Attractive features for preparative organic synthesis and liquid-phase combinatorial synthesis. *J. Org. Chem.*, 61, 6480-6481; Curran, D.P. (1998) Fluorous synthesis: An alternative to organic synthesis and solid phase synthesis for the preparation of small organic molecules. *Canc. J. Sci. Amer.*, 4, S73-S76; Curran, D.P. (1998) Strategy-level separations in organic synthesis: From planning to practice. *Angew. Chem. Int. Ed.*, 37, 1175-1196; Ogawa, A., & Curran, D.P. (1997) Benzotrifluoride: A useful alternative solvent for organic reactions currently conducted in dichloromethane and related solvents. *J. Org. Chem.*, 62, 450-451; Studer, A., Jeger, P., Wipf, P., & Curran, D.P. (1997) Fluorous synthesis: Fluorous protocols for the Ugi and Biginelli multicomponent condensations. *J. Org. Chem.*, 62, 2917-2924; Studer, A., & Curran, D.P. (1997) A strategic alternative to solid phase synthesis: Preparation of a small isoxazoline library by "fluorous synthesis". *Tetrahedron*, 53, 6681-6696; Studer, A., Hadida, S., Ferritto, R., Kim, S.Y., Jeger, P., Wipf, P., & Curran, D.P. (1997) Fluorous synthesis: A fluorous-phase strategy for improving separation efficiency in organic synthesis. *Science*, 275, 823-826. As for all the references herein, these are expressly incorporated by reference in their entirety.

Accordingly, in a preferred embodiment, the invention provides methods for separation of immiscible or partially miscible liquid phases of different density during a parallel extraction, including a fluorous phase organic synthetic process. The methods comprise: (1) positioning a reaction vessel or one or more arrays of reaction vessels, such as one or more microtiter plates, said vessels containing an immiscible or partially miscible liquid phases of different density on the perimeter of a centrifuge rotor in a tilted position; and (2) spinning the rotor of the centrifuge at a speed so that the lower phase is

retained in a "pocket" of the vessels and the upper liquid phase(s) is (are) expelled from the vessels. In the case where only one row of vessels is placed at the perimeter of the centrifuge rotor, the ratio of centrifugal force versus gravitation determines the volume of the "pocket" used for the separation of liquid phases in all vessels and even very low ratio (such as 1:1) can be successfully used. The important factor is only the reproducibility of the speed of centrifugation.

In one embodiment of the invention, the rotor of the centrifuge is spun at a speed so that the centrifugal force on the radius corresponding to the reaction vessels which are closest to the axis of rotation is significantly greater than the force of gravity so that the lower liquid phase is retained in a "pocket" of the vessels and the upper liquid phase(s) is (are) expelled from the vessels. The volume of a "pocket" is determined by: (i) the degree of the tilt, (ii) the speed of rotation, and (iii) the distance of the particular reaction vessel from the axis of rotation. Since it is desired that all reaction vessels in a multivessel arrangement or array of vessels (such as a microtiter plate) should undergo the removal of the upper liquid phase to the same degree, it is important that the angle of the liquid surface in the "pocket" of the reaction vessels during the centrifugation is as close to 90 degrees with respect to the axis of rotation as possible. As used in the present application, the term "significantly greater than the force of gravity" is intended to mean that the force is at least about 5 to 300 X G, preferably about 10 to 300 X G, and even more preferably about 100 to 300 X G. In other words, the centrifuge is spun at a speed so that the ratio of the centrifugal force to gravity, i.e., the Relative Centrifugal Force (RCF) is at least about 5 to 300, preferably about 10 to 300, and more preferably about 100 to 300. Values of RCF significantly greater than 1 are required if individual vessels are placed at different distances from the center of rotation. To achieve uniform distribution of liquid in all vessels it is important to remove as much as possible of the upper liquid phase from all wells. The theoretical value of an angle of liquid surface achievable in the centrifuge versus liquid in nondisturbed state is 90 degrees. This requires a value of the above mentioned ratio (RCF) reaching infinity. For practical reasons, the difference between 89 degrees (ratio 100:1) or 85 degrees (ratio 18:1) may be acceptable. Acceptability of this value depends on the degree of the tilt determining the absolute value of the "pocket" volume. The greater the tilt, the bigger the "pocket" volume, and the bigger the tolerance to the different ratio values at different radiuses. The maximal possible value of the tilt in "fixed tilt" centrifuges is 45 degrees, however, this tilt is completely impractical because the maximal volume of liquid in the well is equal to the volume of the theoretical "pocket".

Higher tilt is possible in the case of "dynamically adjustable tilt" centrifuges (centrifuges in which plate is horizontal in standstill state and "swings out" to a limited position during rotation). According to one mode of one embodiment of the method of the invention, when the reaction vessels used are one or more arrays of regular wells in a microtiter plate, the rotor of the centrifuge is spun at a speed so that the centrifugal force on the radius of wells closest to the axis of rotation is about 5 to 300 X G, preferably about 10 to 300 X G, and more preferably about 100 to 300 X G; and the angle of tilt of the plate is about 1 to 45, preferably 5 to 20, and more preferably 5 to 15 degrees. According to another

mode of this embodiment of the method of the invention, when the reaction vessels used are one or more arrays of microwells in a microtiter plate, the rotor of the centrifuge is spun at a speed so that the centrifugal force on the radius of wells closest to the axis of rotation is about 5 to 300 X G, preferably about 10 to 300 X G, and more preferably about 100 to 300 X G and the angle of tilt of the plate is about 2 to 25, preferably 2 to 10 degrees. In one embodiment, the upper liquid phase is collected on the wall of the centrifuge. In an alternative embodiment, the upper liquid phase is collected in a "collecting pocket" or a series of "collecting pockets". Fig. 1 illustrate retention of lower liquid layer in a "pocket" of the vessels and expulsion of upper liquid layer achieved according to the method of the invention. Fig 2 illustrates the path of upper liquid layer removed from a vessel, such as a well of a microtiter plate by centrifugation. The straight lip at the upper end of each well of the microtiter plate prevents the liquid from entering the well closer to the edge of a centrifugal plate - this well is higher and the lip wall is tilted in the direction to the bottom of the plate. The large arrow represents the vector resulting from centrifugal and gravitational forces. The small arrow with thin trailing line illustrates the direction of the flow of liquid removed from the reaction vessels. Fig. 3 illustrates an alternative embodiment of the invention in which a vessel having a lip facing inward when spun according to the method of the invention "creates" a "pocket" in which the lower liquid phase is retained. The left portion of Fig. 1 illustrates the lower liquid phase and upper liquid phase in the vessel prior to centrifugation. The right portion of Fig. 1 illustrates the pocket containing retained lower liquid phase layer during spinning (and removal of the upper liquid layer). As detailed above, a single reaction vessel, a single microtiter plate or a plurality of microtiter plates can be used in the process of the present invention.

In addition to differential phase synthesis, the present invention finds use in "reverse tilt" synthesis reactions. In this embodiment, the reaction vessels, for example in a microtiter plate format, are tilted in the direction away from the axis of rotation: that is, the open end of the reaction vessel is pointed away from the axis of rotation. The negative (or "reverse") tilt (tilt in the direction away from the axis of rotation) allows for the removal of all liquid content of the well. This may be done for a variety of reasons. In a first embodiment, this may be applicable for washing of wells, e.g. in biological assays when binding to the surface (or modified surface) is studied and removal of the excess of the reagents by repetitive washing is required.

A preferred embodiment for the use of "reverse" tilt is the situation wherein the synthesis is performed on material firmly attached to the well; that is, the material will not be expelled from the reaction vessel under the centrifugation conditions used in the process. In a preferred embodiment, the material can be a "tea-bag" type of material filled with the solid support on which the synthesis is done, or a textile like material; for examples of these supports see U.S. Patent No. 5,202,418, hereby expressly incorporated by reference.

In a preferred embodiment, the synthesis is performed on one or more modified surface(s) of the

reaction vessel itself. In this embodiment, rather than use a solid support such as a microbead or a dense phase as the support for a synthetic reaction, the actual surface of the reaction vessel is used as the solid phase for synthetic reactions; liquid reagents are added, reacted, and then the residual liquid is removed via centrifugation. That is, the reaction vessel, such as a microtiter plate, may be functionalized as a solid support for the synthesis. In this embodiment, the reaction vessel may be any material that can be modified to allow synthesis; possible materials for substrates include, but are not limited to, glass and modified or functionalized glass, plastics (including acrylics, polystyrene and copolymers of styrene and other materials, polypropylene, polyethylene, polybutylene, polyurethanes, Teflon, etc.), polysaccharides, nylon or nitrocellulose, resins, silica or silica-based materials including silicon and modified silicon, carbon, metals, inorganic glasses, and plastics, and a variety of other polymers.

The functionalization of solid support surfaces such as certain polymers with chemically reactive groups such as thiols, amines, carboxyls, etc. is generally known in the art. Some examples of these surface chemistries for subsequent addition of building blocks include, but are not limited to, amino groups including aliphatic and aromatic amines, carboxylic acids, aldehydes, amides, chloromethyl groups, hydrazide, hydroxyl groups, sulfonates and sulfates.

These functional groups can be used to add any number of different building block moieties to the vessels, generally using known chemistries, including, but not limited to the use of amino-functionalized supports, sulfhydryl linkers, etc. There are a number of sulfhydryl reactive linkers known in the art such as SPDP, maleimides, α -haloacetyls, and pyridyl disulfides (see for example the 1994 Pierce Chemical Company catalog, technical section on cross-linkers, pages 155-200, incorporated herein by reference). Similarly, amino groups on the building blocks and on the surface can be attached using linkers; for example, a large number of stable bifunctional groups are well known in the art, including homobifunctional and heterobifunctional linkers (see Pierce Catalog and Handbook, pages 155-200). In an additional embodiment, carboxyl groups (either from the surface or from the building block) may be derivatized using well known linkers (see the Pierce catalog). For example, carbodiimides activate carboxyl groups for attack by good nucleophiles such as amines (see Torchilin et al., Critical Rev. Therapeutic Drug Carrier Systems, 7(4):275-308 (1991), expressly incorporated herein). In addition, preferred methods include systems that allow post-synthesis cleavage from the reaction vessels.

As will be appreciated by those in the art, the functionalization will depend on the synthesis done, as outlined below.

As will be appreciated by those in the art, in the reverse tilt embodiments, virtually any solid phase synthesis reaction may be done. Preferred embodiments include organic syntheses, including, but not limited to, peptide synthesis, nucleic acid synthesis, and small molecule synthesis.

In a preferred embodiment, peptides are synthesized. By "peptide" herein is meant at least two amino acids joined via a peptide bond. The peptide may be made up of naturally occurring amino acids and peptide bonds, or synthetic peptidomimetic structures. The side chains may be in either the (R) or the (S) configuration. In the preferred embodiment, the amino acids are in the (S) or L-configuration. If non-naturally occurring side chains are used, non-amino acid substituents may be used, for example to prevent or retard in vivo degradations.

The stepwise solid phase synthesis of peptides is well known. An exemplary solid-phase combinatorial protocol is that for the synthesis of peptides attached to polymer resin, which proceeds according to Lam et al., 1991, *Nature* 354:82-84; U.S. Patent 5,510,240; Lam et al., 1994, *Selectide technology: Bead-binding screening. Methods: A Companion to Methods in Enzymology* 6:372-380. Another exemplary protocol is that for the synthesis of benzodiazepine moieties, which proceeds according to Bunin et al., 1992, *J. Amer. Chem. Soc.*, 114:10997-10998 and U.S. Patent 5,288,514. Also, for protocols for the addition of N-substituted glycines to form peptoids, see, e.g., Simon, et al., 1992, *Proc. Natl. Acad. Sci. USA*, 89:9367-9371; Zuckermann et al., 1992, *J. Amer. Chem. Soc.*, 114:10646-10647; WO PCT94/06,451 to Moos et al.; Approaches for synthesis of small molecular libraries were recently reviewed by, e.g., Krchnak and Lebl, 1996, *Molecular Diversity*, 1:193-216; Ellman, 1996, *Account. Chem. Res.*, 29:132-143; Armstrong et al., 1996, *Account. Chem. Res.*, 29:123-131; Fruchtel et al., 1996, *Angew. Chem. Int. Ed.*, 35:17-42; Thompson et al., 1996, *Chem. Rev.*, 96:555-600; Rinnova et al., 1996, *Collect. Czech. Chem. Commun.*, 61: 171-231; Hermkens et al., 1996, *Tetrahedron*, 52:4527-4554. Exemplary building blocks and reagents are amino acids, nucleosides, other organic acids, aldehydes, alcohols, and so forth, as well as bifunctional compounds, such as those given in Krchnak and Lebl, 1996, *Molecular Diversity*, 1:193-216.

In a preferred embodiment, the methods and compositions of the invention are used to synthesize nucleic acids. By "nucleic acid" or "oligonucleotide" or grammatical equivalents herein means at least two nucleotides covalently linked together. A nucleic acid of the present invention will generally contain phosphodiester bonds, although in some cases, as outlined below, nucleic acid analogs are included that may have alternate backbones, comprising, for example, phosphoramidate (Beaucage et al., *Tetrahedron* 49(10):1925 (1993) and references therein; Letsinger, *J. Org. Chem.* 35:3800 (1970); Sprinzl et al., *Eur. J. Biochem.* 81:579 (1977); Letsinger et al., *Nucl. Acids Res.* 14:3487 (1986); Sawai et al., *Chem. Lett.* 805 (1984); Letsinger et al., *J. Am. Chem. Soc.* 110:4470 (1988); and Pauwels et al., *Chemica Scripta* 26:141 (1986)), phosphorothioate (Mag et al., *Nucleic Acids Res.* 19:1437 (1991); and U.S. Patent No. 5,644,048), phosphorodithioate (Briu et al., *J. Am. Chem. Soc.* 111:2321 (1989)), O-methylphosphoramidite linkages (see Eckstein, *Oligonucleotides and Analogues: A Practical Approach*, Oxford University Press), and peptide nucleic acid backbones and linkages (see Egholm, *J. Am. Chem. Soc.* 114:1895 (1992); Meier et al., *Chem. Int. Ed. Engl.* 31:1008 (1992); Nielsen, *Nature*, 365:566 (1993); Carlsson et al., *Nature* 380:207 (1996), all of which are incorporated by reference). Other analog nucleic acids include those with positive backbones (Denpoy et al., *Proc. Natl. Acad. Sci.*

5 USA 92:6097 (1995); non-ionic backbones (U.S. Patent Nos. 5,386,023, 5,637,684, 5,602,240, 5,216,141 and 4,469,863; Kiedrowshi et al., *Angew. Chem. Intl. Ed. English* 30:423 (1991); Letsinger et al., *J. Am. Chem. Soc.* 110:4470 (1988); Letsinger et al., *Nucleoside & Nucleotide* 13:1597 (1994); Chapters 2 and 3, *ASC Symposium Series 580, "Carbohydrate Modifications in Antisense Research"*, Ed. Y.S. Sanghui and P. Dan Cook; Mesmaeker et al., *Bioorganic & Medicinal Chem. Lett.* 4:395 (1994); Jeffs et al., *J. Biomolecular NMR* 34:17 (1994); *Tetrahedron Lett.* 37:743 (1996)) and non-ribose backbones, including those described in U.S. Patent Nos. 5,235,033 and 5,034,506, and Chapters 6 and 7, *ASC Symposium Series 580, "Carbohydrate Modifications in Antisense Research"*, Ed. Y.S. Sanghui and P. Dan Cook. Nucleic acids containing one or more carbocyclic sugars are also included within the definition of nucleic acids (see Jenkins et al., *Chem. Soc. Rev.* (1995) pp169-176). Several nucleic acid analogs are described in Rawls, *C & E News* June 2, 1997 page 35. All of these references are hereby expressly incorporated by reference. These modifications of the ribose-phosphate backbone may be done to increase the stability and half-life of such molecules in physiological environments.

15 As will be appreciated by those in the art, all of these nucleic acid analogs may find use in the present invention. In addition, mixtures of naturally occurring nucleic acids and analogs can be made; alternatively, mixtures of different nucleic acid analogs, and mixtures of naturally occurring nucleic acids and analogs may be made.

20 The nucleic acids may contain any combination of deoxyribo- and ribo-nucleotides, and any combination of bases, both naturally occurring and synthetic, including uracil, adenine, thymine, cytosine, guanine, inosine, xanthine hypoxanthine, isocytosine, isoguanine, etc. A preferred embodiment utilizes isocytosine and isoguanine in nucleic acids designed to be complementary to other probes, rather than target sequences, as this reduces non-specific hybridization, as is generally described in U.S. Patent No. 5,681,702. As used herein, the term "nucleoside" includes nucleotides as well as nucleoside and nucleotide analogs, and modified nucleosides such as amino modified nucleosides or phosphoramidite nucleosides. In addition, "nucleoside" includes non-naturally occurring analog structures. Thus for example the individual units of a peptide nucleic acid, each containing a base, are referred to herein as a nucleoside.

30 The stepwise synthesis of nucleic acids is well known, and generally involves the stepwise addition of protected, activated nucleoside monomers to a solid support, followed by deprotection steps and washing steps. See generally Gait, *Oligonucleotide Synthesis: A Practical Approach*, IRL Press, Oxford, UK 1984; Eckstein, incorporated by reference. This is generally done either with phosphoramidite or H-phosphonate nucleosides. This is generally done in one of two ways. First, the 5' position of the ribose is protected with 4',4-dimethoxytrityl (DMT) followed by reaction with either 2-cyanoethoxy-bis-diisopropylaminophosphine in the presence of diisopropylammonium tetrazolide, or by reaction with chlorodiisopropylamino 2'-cyanoethoxyphosphine, to give the phosphoramidite as is

known in the art; although other techniques may be used as will be appreciated by those in the art. See Gait, *supra*; Caruthers, *Science* 230:281 (1985), both of which are expressly incorporated herein by reference.

In a preferred embodiment, the reverse tilt method is used to synthesize small organic molecules. As will be appreciated by those in the art, the literature contains numerous examples of the synthesis of a variety of small molecules, particularly libraries of small molecules on solid-phase supports; see for example Pavia et al., *Bioorganic & Medicinal Chemistry* 1996 4(5):659-666; Liskamp et al., *Bioorganic & Medicinal Chemistry* 1996 4(5):667-672; Tong et al., *Bioorganic & Medicinal Chemistry* 1996 4(5):693-698; Houghten et al., *Bioorganic & Medicinal Chemistry* 1996 4(5):709-715; Freier et al., *Bioorganic & Medicinal Chemistry* 1996 4(5):717-725; Bolton et al., *Tetrahedron Letters* 1996 37(20) 3433-3436, all of which are hereby expressly incorporated by reference.

In addition, for all the reverse tilt embodiments herein, it may be desirable to use linkers to attach the first building blocks to the surface.

Accordingly, the invention provides methods of synthesis using reverse tilt centrifugation. In this embodiment, a reaction vessel or array of vessels are provided that comprise either a pre-functionalized first building block or the chemistry to attach the first building block of the molecule to be made. Subsequently, a plurality of building block addition steps are performed, all of which involve repetitive execution of the following substeps, and in a sequence chosen to synthesize the desired compound. First a sufficient quantity of a solution containing the building block moiety selected for addition is accurately added to the reaction vessels so that the building block moiety is present in a molar excess to the intermediate compound. The reaction is triggered and promoted by activating reagents and other reagents and solvents as needed, which are also added to the reaction vessel. The reaction vessel is then incubated at a controlled temperature for a time, typically between 5 minutes and 24 hours, sufficient for the building block addition reaction or transformation to go to substantial completion. Optionally, during this incubation, the reaction vessel can be intermittently agitated or stirred. Finally, in a last substep of building block addition, the reaction vessel is prepared for addition of the next building block by removing the reaction fluid using the "reverse tilt" centrifugation steps outlined herein and thorough washing and reconditioning as needed. Washing typically involved three to seven cycles of adding and removing a wash solvent. Optionally, during the addition steps, multiple building blocks can be added to one reaction vessel in order to synthesize a mixture of compound intermediates attached to one reaction vessel. After the desired number of building block addition steps, the final compound is present in the reaction vessel. It can then be optionally cleaved from the reaction vessel support; alternatively, the reaction vessels themselves can be used in subsequent reactions. A variety of exemplary reactions are outlined in WO99/25470, hereby incorporated by reference, and include reactions for peptide and synthetic peptides, benzodiazepine and derivatives, peptoids, N-substituted polyamide monomers. Exemplary building

blocks and reagents are amino acids, nucleic acids, other organic acids, aldehydes, alcohols, and so forth, as well as bifunctional compounds.

The present invention also provides apparatus for organic synthesis as outlined herein. The apparatus of the invention comprise a variety of components, including a centrifuge and a rotor. In general, the rotor comprises at least one holder, and preferably a plurality of holders, that each will hold at least a first reaction vessel, and preferably a plurality of reaction vessels.

As will be appreciated by those in the art, the reaction vessels can be configured in a variety of ways. In a preferred embodiment, the reaction vessels are in the form of an array of vessels such as a microtiter plate that contains the individual reaction vessels. Particularly preferred configurations are 96-well and 384-well microtiter plates.

As will be appreciated by those in the art, one of the important aspects of the invention is that one or more liquid phases are expelled from the reaction vessels upon centrifugation. Accordingly, there are two main ways the system may be configured to allow the collection of the expelled liquids.

In a preferred embodiment, the holders adapted to attaching a microtiter plate to a centrifuge rotor can have or comprise a series of collecting pockets to collect and retain the liquid expelled from the vessels during centrifugation. These collecting pockets can comprise one or more indentations or grooves having a volume sufficient to collect and retain any expelled liquid.

In an alternative preferred embodiment, the holder does not have collecting pockets. In the latter situation, the liquid expelled is deposited on the walls of the centrifuge. In this embodiment, the centrifuge is configured such that there is a collecting pocket or reservoir, generally in the bottom of the centrifuge, such that gravity flow of the expelled liquids causes the liquids to pool in the pocket. This may be periodically emptied as needed, and can comprise a port or valve that allows drainage.

Alternatively, the centrifuge is configured to have a tube or pipe leading to a waste reservoir; this tube is also generally at the bottom of the centrifuge. The gravity flow of the expelled liquids can then lead to collection of the waste outside the centrifuge.

In a preferred embodiment, the holder(s) hold the reaction vessels in a tilted position. The holder(s) may either hold one or more of the reaction vessels in a fixed tilted position or in a position in which the angle of tilt can be changed flexibly.

As outlined herein, the tilt of the rotor can be towards the axis of rotation, resulting in the retention of a phase of the reaction. Alternatively, when the synthetic reaction is done on material firmly attached to the reaction vessel (e.g. with a force such that it will not be expelled during the centrifugation) or when

the reaction is done on the reaction vessel itself, the tilt of the rotor can be away from the axis of rotation ("reverse tilt") as described herein.

In a preferred embodiment, each holder contains only one set or array of reaction vessels. Thus, for example, the holder may contain grooves or rails to position the reaction vessels, e.g. microtiter plate, in the holders. Alternatively, the reaction vessels may be "stacked" or "layered". However, placing single sets or arrays of reaction vessels such as individual microtiter plates on the centrifuge perimeter has an advantage of simple interfacing with liquid distribution automats (such as Packard Canberra, Tecan, Hamilton, and others). A liquid distribution device can be placed onto the top of a centrifugal synthesizer. Particularly preferred are liquid distribution systems for simultaneous dispensing in a format that fits the reaction vessel configuration; for example, when the reaction vessels are in the form of a 96 well microtiter plate, the liquid distribution system is preferably a 96 channel device.

The liquid distribution system can also comprise a set of reservoirs and tubes for delivery; for example, the liquid distribution system can have a 96 channel liquid distributor that can deliver solvent or solutions of reagents from different bottles into the plate positioned under the needles of the distributor. For example, for nucleic acid synthesis, preferred embodiments include separate reagent bottles for each nucleoside.

In a preferred embodiment, the liquid distribution system is an integrated system; that is, the liquid is distributed into the reaction vessels when they are present in the centrifuge; the reaction vessels are not removed from the centrifuge for addition of reagents. In general, the liquid distribution system is an integral part of the centrifuge; the liquid is delivered without removing the lid of the centrifuge.

In addition, the apparatus of the invention can further comprise a processor or computer to control the synthesis of the moieties. For example, a computer may be used that processes a program of instructions of stepwise additions of liquid phases, reagents, solvents, washes, etc. to the reaction vessels, followed by centrifugation steps for removal of liquids from the reaction vessels. Thus, the present invention provides methods executed by a computer under the control of a program, the computer including a memory for storing the program. The program is directed to the addition of reagents to the reaction vessels using the liquid distribution system, allowing incubation as needed, and removing unreacted reagents and liquid by centrifugation for a defined time at a defined speed, with wash steps and repetition as required.

In addition to the components mentioned above, the centrifuge may also comprise additional components. For example, the centrifuge can comprise a sensor to signal the computer and liquid distribution system when a set of reaction vessels in a particular orientation, and a motor to rotate the rotor into the correct orientation for liquid delivery, also in control of the computer. Furthermore, in the case of adjustable tilt holders or rotors, the centrifuge can utilize a control and a sensor to control the

degree of tilt.

The integrated device is useful as a "centrifugation synthesizer" for fluorous phase synthetic processes.

The methods and apparatus of the invention find use in a number of applications, as outlined herein.

5 In a preferred embodiment, the methods and apparatus of the present invention are advantageously useful for the manual or automated preparation of combinatorial libraries or megaarrays of compounds by fluorous phase organic synthesis. As is well known to those skilled in the art, such combinatorial libraries or megaarrays have numerous uses, in particular, for the selection of pharmaceutical lead compounds, for the optimization of pharmaceutical lead compounds and for the identification and/or
10 isolation of pharmaceutical drugs. The methods and apparatus of the invention for liquid/liquid phase separation can also advantageously be used for parallel extraction and purification of compound arrays synthesized or obtained by other methods. Other applications in analytical chemistry (extraction, desalting or other means of parallel preparations of samples), biochemistry (parallel processing of samples) are envisioned.

15 The use of complete removal of liquid from the arrays of vessels can be applied in the biological screening where binding to the surface of the vessels (modified surface by attached reagent or cell culture) is investigated. In this case the tilt of the vessel during the centrifugation is "reversed", i.e. no "pocket" is formed during the centrifugation. In this case, for example, any number of binding assays may be done. For example, ELISA type assays are frequently done in a microtiter plate format, where
20 antibodies are attached using a variety of known chemistries. The addition of sample(s) and additional reagent components, with washing as required, may utilize the present invention. Furthermore, in this embodiment, the apparatus may comprise additional components such as fluorescence readers.

Similarly, reverse tilt reactions can be used in synthetic reactions as outlined above, with particular emphasis on nucleic acid and peptide synthesis.

25

**EXAMPLE: REMOVAL OF UPPER LAYER LIQUID PHASE WITHOUT
TRANSFER OF LOWER LAYER LIQUID PHASE**

30 Ten percent solution of ethanol in water saturated with toluene was distributed into wells of microtiterplate (40 uL per well). Ethyl acetate (150 uL) was repeatedly distributed into the wells and microtiterplates were shaken for 1 minute and centrifugated in tilted arrangement. Figure 5 shows UV spectra of wells before and after two steps of parallel extraction proving complete elimination of contamination by aromatic hydrocarbon.

WHAT IS CLAIMED:

1. A method for elimination of a liquid phase from at least one reaction vessel comprising:
 - (a) positioning a plurality of reaction vessels containing a liquid or mixture of liquids in a holder on the perimeter of a centrifuge rotor in a tilted position with a tilt away from the axis of rotation; and
 - (b) spinning the rotor of the centrifuge at a speed so that the liquid is expelled from said vessels.
2. A method according to claim 1 wherein the method of elimination is employed during solid-phase organic synthesis.
3. The method according to claim 2 wherein said solid-phase organic synthesis is synthesis of peptides.
4. The method according to claim 2 wherein said solid-phase organic synthesis is synthesis of nucleic acids.
5. The method according to claim 1, further comprising repeating steps (a) and (b), whereby an organic molecule is synthesized.
6. The method according to claim 1 wherein said reaction vessel comprises at least one microtiter plate.
7. A method according to claim 1, wherein said rotor comprises a plurality of holders.
8. A method according to claim 1 wherein said holder comprises at least one collection pocket having a volume sufficient to collect and retain any liquid expelled from said vessels.
9. A method according to claim 1 wherein said expelled liquid is collected in a waste reservoir connected to said centrifuge by a tube.
10. A method of synthesis of compounds, said method comprising:
 - (a) providing a reaction vessel containing a first building block coupled to said vessel;
 - (b) positioning said vessel in a holder on the perimeter of a centrifuge rotor;
 - (c) adding a second building block to said vessel; and
 - (d) spinning said rotor at a speed sufficient to expel said liquid from said vessel.
11. A method according to claim 10 wherein said reaction vessel is tilted away from the axis of

rotation.

12. A method according to claim 10 wherein said reaction vessel is part of a microtiter plate.
13. A method according to claim 10 further comprising repeating steps (c) and (d) whereby an organic moiety is synthesized.
- 5 14. A method according to claim 10 further comprising washing said solid support prior to adding additional building blocks.
- 15 15. A method according to claim 10 wherein said building blocks are amino acids.
16. A method according to claim 10 wherein said building blocks are nucleosides.
- 10 17. A method for separating at least two immiscible or partially miscible liquids comprising:
 - (a) positioning a plurality of reaction vessels containing said liquids in a holder on the perimeter of a centrifuge rotor; and
 - (b) spinning the rotor of the centrifuge at a speed such that the lower layer of the multiphase system is retained in a "pocket" of the vessels and the upper layer is expelled
- 15 18. The method of claim 17 wherein said plurality of reaction vessels comprise a microtiter plate.
19. The method of claim 17 wherein said rotor comprises a plurality of holders.
20. The method of claim 17 wherein said holder comprises at least one collection pocket having a volume sufficient to collect and retain any liquid expelled from said vessels.
- 20 21. The method of claim 17 wherein said upper layer is collected in a waste reservoir attached to said centrifuge with a tube.
22. The method of claim 17 wherein said holder holds said reaction vessels in a tilted position toward the center of rotation.
- 25 23. The method of claim 22 wherein the angle of tilt is less than 25 degrees.
24. The method of claim 22 wherein said rotor is spun at a speed at which the centrifugal force on the radius corresponding to the vessels which are closest to the axis of rotation is substantially greater than the force of gravity, so that the lower layer of the multi-phase system fills the "pocket" of the

vessels and the upper layer of the multilayer system is expelled from the vessels.

25. The method according to claim 22, in which the rotor of the centrifuge is spun at a speed at which the centrifugal force on the radius corresponding to the reaction vessels closest to the axis of rotation is at least 20 x G.

5 26. The method according to claim 22, in which the rotor of the centrifuge is spun at a speed at which the centrifugal force on the radius corresponding to the reaction vessels closest to the axis of rotation is at least 5 to 300 X G.

27. An apparatus comprising a centrifuge comprising:

- 10 a) a rotor designed to hold reaction vessels at a tilt away from the axis of rotation;
and
b) a waste reservoir connected to said centrifuge to hold liquids expelled from said reaction vessels.

28. An apparatus according to claim 27 wherein said waste reservoir is connected to said centrifuge with a tube.

15 29. An apparatus according to claim 27 wherein said rotor comprises a plurality of holders, each holder designed to hold at least one microtiter plate.

30. An apparatus according to claim 27 further comprising a liquid distribution system.

31. An apparatus according to claim 30 wherein said liquid distribution system is integrated into the centrifuge.

20 32. An apparatus according to claim 27 further comprising a computer.





FIG. 1



3/4




FIG. 3




FIG. 5A





FIG. 5B



THIS PAGE BLANK (USPTO)

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
3 August 2000 (03.08.2000)

PCT

(10) International Publication Number
WO 00/44491 A3

(51) International Patent Classification⁷: B01J 19/00,
B04B 5/04

(21) International Application Number: PCT/US00/02233

(22) International Filing Date: 28 January 2000 (28.01.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/118,377 29 January 1999 (29.01.1999) US

(71) Applicant: ILLUMINA, INC. [US/US]; Suite 200, 9390
Towne Centre Drive, San Diego, CA 92121 (US).

(72) Inventor: LEBL, Michael; 6161 Arnoldson Court, San
Diego, CA 92122 (US).

(74) Agents: BREZNER, David, J. et al.; Flehr Hohbach Test
Albritton & Herbert LLP, Suite 3400, 4 Embarcadero Cen-
ter, San Francisco, CA 94111-4187 (US).

(81) Designated States (national): AE, AL, AM, AT, AU, AZ,
BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK,

DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,
IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,
LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO,
RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG,
UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent
(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent
(AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU,
MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GW, ML, MR, NE, SN, TD, TG).


Published:

- With international search report.
- Before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments.

(88) Date of publication of the international search report:
21 December 2000

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: CENTRIFUGING APPARATUS AND METHOD FOR SEPARATION OF LIQUID PHASES AND ORGANIC SYN-
THESIS



(57) Abstract: A simple, efficient apparatus and method for separating layers of immiscible or partially miscible liquids useful in methods of high-throughput combinatorial organic synthesis or parallel extraction of large libraries or megaarrays of organic compounds is disclosed. The method comprises: (a) positioning a plurality of reaction vessels containing a liquid or mixture of liquids in a holder on the perimeter of a centrifuge rotor in a tilted position with a tilt away from the axis of rotation; and (b) spinning the rotor of the centrifuge at a speed so that the liquid is expelled from said vessels. In a preferred embodiment, an apparatus and method for separating layers of immiscible or partially miscible liquids compatible with microtiter plate type array(s) of reaction vessels is disclosed. Another application of centrifugation based liquid removal was found for washing the plates in biological assays or synthesis on modified substrates.

WO 00/44491 A3

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 00/02233

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B01J19/00 B04B5/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B01J B04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	LEBL M: "A New Approach to Automated Solid Phase Synthesis Based on Centrifugation of Tilted Plates" JOURNAL OF THE ASSOCIATION FOR LABORATORY AUTOMATION, vol. 3, no. 3, July 1998 (1998-07), pages 59-61, XP000920813 the whole document	1,2,5-7, 17-19, 22-26
Y		9,21, 27-32 10-16
A		
Y	GB 1 241 539 A (AMERICAN HOSPITAL SUPPLY CORP.) 4 August 1971 (1971-08-04) page 4, line 55 - line 60; figure 3	9,21, 27-32
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *G* document member of the same patent family

Date of the actual completion of the international search

10 October 2000

Date of mailing of the international search report

19. 10. 2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Veefkind, V

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 00/02233

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 445 915 A (CESKOSLOVENSKA AKADEMIE VED) 11 September 1991 (1991-09-11) page 4, line 31 - line 41	10,13-15
A	page 5, line 18 - line 30; figures 2,3; examples 4-9	16,27
A	WO 90 05590 A (INST MOLEKULARBIOLOGIE AK) 31 May 1990 (1990-05-31) abstract; figures 1-3	1,8,17, 22,23, 27,28
A	US 3 586 484 A (ANDERSON NORMAN G) 22 June 1971 (1971-06-22) column 3, line 35 - line 67; figures 2-6	1,8,17, 20,22,23
A	US 5 089 417 A (WOGOMAN FRANK W) 18 February 1992 (1992-02-18) column 5, line 20 - column 12, line 51; figures 1-7	1,17
A	FR 2 156 519 A (IMMUNO AG) 1 June 1973 (1973-06-01) figures 1,2	1,6,12, 17,18, 27,29
A	EP 0 569 115 A (GEN ATOMICS) 10 November 1993 (1993-11-10) the whole document	1,4,6, 12,17, 18,27,29
P,X	WO 99 25470 A (TREGA BIOSCIENCES INC) 27 May 1999 (1999-05-27) cited in the application the whole document	1-8, 17-20, 22-26

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US 00/02233

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this International application, as follows:

see additional sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☒ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-9, 17-26

Independent claim 1 and dependent claims 2-9, relating to a method for elimination of a liquid phase from at least one reactor vessel using a centrifuge with tilted vessels.

Independent claim 17 and dependent claims 18-26, relating to a method for separating at least two liquids by spinning a rotor with reactor vessels at such speed that a lower layer is retained in a "pocket" of the vessels and the upper layer is expelled.

2. Claims: 10-16

Independent claim 10 and dependent claims 11-16, relating to a method of synthesis of compounds, using a first building block coupled to a vessel, positioning in centrifuge, adding second building block and centrifuging to expel said liquid from said vessel.

3. Claims: 27-32

Independent claim 27 and dependent claims 28-32, relating to a centrifuge with a waste reservoir connected to it.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/02233

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB 1241539	A	04-08-1971	CH 503996 A DE 2026759 A	28-02-1971 06-05-1971
EP 0445915	A	11-09-1991	CS 9000508 A AT 126233 T CA 2035527 A DE 69111856 D JP 6056900 A US 5202418 A US 5342585 A US 5338831 A	15-10-1991 15-08-1995 03-08-1991 14-09-1995 01-03-1994 13-04-1993 30-08-1994 16-08-1994
WO 9005590	A	31-05-1990	SU 1704838 A JP 3502302 T SE 9002411 A	15-01-1992 30-05-1991 11-07-1990
US 3586484	A	22-06-1971	AT 303424 B BE 750657 A CH 519170 A DE 2022084 A ES 378828 A FR 2043636 A GB 1260804 A IT 954068 B JP 49020116 B NL 7007331 A SE 367061 B SU 365081 A	15-10-1972 03-11-1970 15-02-1972 26-11-1970 16-07-1972 19-02-1971 19-01-1972 30-08-1973 22-05-1974 25-11-1970 13-05-1974 28-12-1972
US 5089417	A	18-02-1992	US 4892708 A AU 596017 B AU 1850488 A CA 1310624 A DE 3882828 A DE 3882828 T EP 0297394 A ES 2041739 T IL 86398 A JP 1025058 A	09-01-1990 12-04-1990 05-01-1989 24-11-1992 09-09-1993 11-11-1993 04-01-1989 01-12-1993 29-03-1992 27-01-1989
FR 2156519	A	01-06-1973	AT 308712 B DE 2201542 A DE 7138794 U	15-06-1973 12-04-1973 27-01-1972
EP 0569115	A	10-11-1993	JP 6034628 A	10-02-1994
WO 9925470	A	27-05-1999	US 6121054 A AU 1415499 A EP 1032469 A	19-09-2000 07-06-1999 06-09-2000

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)